

APP CRS
077°

Rwy Ldg **10000**
TDZE **29**
Apt Elev **29**

RNAV (RNP) Y RWY 8
JACKSONVILLE INTL (JAX)

▼

For uncompensated Baro-VNAV systems, procedure NA below -5°C (23°F) or above 54°C (130°F). GPS required. For inop MALSR, increase RNP 0.11 all Cats visibility to 1 mile, increase RNP 0.30 all Cats visibility to 1½ mile.

ALSF-2

MISSED APPROACH: Climb to 2000 on track 077° to YEJWO and hold.

D-ATIS 125.85	JACKSONVILLE APP CON 119.0 269.9	JACKSONVILLE TOWER 118.3 317.7	GND CON 121.9 348.6
-------------------------	--	--	-------------------------------

VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 70).

GRNDN
1100

GP 3.00°
TCH 51

077°

RW08

3.2 NM

See planview for multiple IF locations.

2000

↑

tr 077°

YEJWO

CATEGORY	A	B	C	D
RNP 0.11 DA		356/40	327 (400-¾)	
RNP 0.30 DA		426/45	397 (400-¾)	

AUTHORIZATION REQUIRED

REIL Rwy 32

TDZL/RCLS Rwy 8, 14, and 26

HIRL Rwy 8-26 and 14-32

JACKSONVILLE, FLORIDA

Orig-B 30APR15

30°30'N-81°41'W

JACKSONVILLE INTL (JAX)

RNAV (RNP) Y RWY 8