

WAAS CH 50309 W22A	APP CRS 218°	Rwy Idg 5420 TDZE 161 Apt Elev 163
--	------------------------	---

RNAV (GPS) RWY 22

MC MINNVILLE MUNI (MMV)

RNP APCH.

▼

Baro-VNAV NA when using Aurora State altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C or above 48°C. When local altimeter setting not received, use Aurora State altimeter setting; increase LPV DA to 534 feet, LNAV/VNAV DA to 703 feet; increase all MDAs 60 feet and visibility LNAV Cats C and D ½ SM. For inop ALS, increase LPV all Cats visibility to ¾ SM, LNAV/VNAV all Cats to 1 ¾ SM, LNAV Cat A/B to 1 SM and Cat C/D to 1 ¾ SM. For inop ALS when using Aurora State altimeter setting, increase LNAV/VNAV all Cats visibility to 1 ¾ SM, LNAV Cat A/B to 1 SM and Cat C/D to 1 ¾ SM. VDP NA when using Aurora State altimeter setting.

MAISLR

AS


15

15


15

MISSED APPROACH:
Climb to 4900 direct
OVUGE then on 218°
track to PUCIV and hold,
continue climb-in-hold to
4900.

ASOS 135.675	PORTLAND APP CON 126.0 284.6 (NORTH)	SEATTLE CENTER 125.8 291.7 (SOUTH)	CLNC DEL 118.35	UNICOM 123.0 (CTAF) 1
------------------------	--	--	---------------------------	---------------------------------



4900	OVUGE	218° tr	PUCIV	UNECE	038°	2900	4 NM Holding Pattern	
* LNAV only				KIGKE 2.8 NM to RW22	LYEV 1900	218°	2500	GP 3.00° TCH 57
RW22				* 1.7 NM to RW22	1100*	1900		
1.7				1.1	2.4 NM	3.8 NM	2.5 NM	
CATEGORY	A		B		C		D	
LPV DA	474-¾ 313 (400-¾)							
LNAV/ VNAV DA	643-1¼ 482 (500-1¼)							
LNAV MDA	740-¾ 579 (600-¾)				740-1¼ 579 (600-1¼)			



NW-1, 06 AUG 2026 to 03 SEP 2026

NW-1, 06 AUG 2026 to 03 SEP 2026