



LOC/DME I-LLT 110.1 Chan 38	APP CRS 341°	Rwy Ldg TDZE 4365 Apt Elev 4365
---	------------------------	---

ILS or LOC RWY 34
NORTHEAST WYOMING RGNL (GCC)

ADF or DME required.		MALSR 	MISSED APPROACH: Climb to 5700 then climbing left turn to 7000 on heading 150° and on GCC VOR/DME R-293 to GCC VOR/DME and hold, continue climb-in-hold to 7000.	
▼ ▲ Circling Rwy 3 NA at night. For inop ALS when using GILYE FIX minimums, increase Cat C/D visibility to 1½ SM.				
ASOS 124.175	DENVER CENTER 135.6 363.025		UNICOM 122.95	CTAF 118.5 



5700	7000	GCC R-293	GCC	DERYK NDB I-LLT 5.4	VGSI and ILS glidepath not coincident. (VGSI Angle 3.20/TCH 56)
Use I-LLT DME when on the LOC course.					
*LOC only	I-LLT 1.4	*HLLT 3	GILYE HLLT 3.8	5710	161°
5240*				5800	341°
1.6 NM				0.8	1.6 NM
CATEGORY	A	B	C	D	
S-ILS 34	4565-½ 200 (200-½)				
S-LOC 34	5240-½ 875 (900-½)	5240-¾ 875 (900-¾)	5240-2	875 (900-2)	
CIRCLING	5240-1¼	875 (900-1¼)	5400-3	1035 (1100-3)	
GILYE FIX MINIMUMS					
S-LOC 34	4940-½	575 (600-½)	4940-1¼	575 (600-1¼)	
CIRCLING	5040-1	5240-1¼ 875 (900-1¼)	5400-3	1035 (1100-3)	

NW-1, 06 AUG 2026 to 03 SEP 2026

NW-1, 06 AUG 2026 to 03 SEP 2026