

WAAS
CH **93835**
W22A

APP CRS
220°

Rwy Ldg
TDZE **182**
Apt Elev **182**

RNAV (GPS) RWY 22

DEXTER B FLORENCE MEML FLD (ADF')


▼

▲ NA

DME/DME RNP-0.3 NA. When local altimeter setting not received, use Hot Springs altimeter setting and increase all MDAs 120 feet, and increase LP and LNAV Cat C visibility ⅔ SM and Circling Cat C visibility ½ mile. Night landing: Rwy 22 NA. Helicopter visibility reduction below 1 SM NA.

MISSED APPROACH: Climb to 2000 direct CUBUG and hold.

AWOS-3PT 118.175	MEMPHIS CENTER 128.475 377.15	UNICOM 122.7 (CTAF) 0
----------------------------	---	---------------------------------



2000 CUBUG		Visual Segment - Obstacles.			
		→ 1.7 → 3.9 NM → 5 NM →			
CATEGORY		A	B	C	D
LP MDA		600-1	418 (500-1)	600-1⅓ 418 (500-1⅓)	NA
LNAV MDA		680-1	498 (500-1)	680-1⅓ 498 (500-1⅓)	NA
CIRCLING		760-1 578 (600-1)	800-1 618 (700-1)	1040-2½ 858 (900-2½)	NA

