

WAAS CH 66043 W06A	APP CRS 055°	Rwy Ldg TDZE 435 Apt Elev 435	3693
--	------------------------	---	-------------

RNAV (GPS) RWY 6

NEW GARDEN (N57)

RNP APCH.

V

NA

VDP NA when using New Castle altimeter setting. Obtain local altimeter setting on CTAF; when local altimeter setting not received, use New Castle altimeter setting and increase all MDA 80 feet. Increase LP Cat C visibility $\frac{3}{8}$ SM, LNAV Cat C visibility $\frac{1}{4}$ SM and Circling Cat C visibility $\frac{1}{4}$ SM.

MISSED APPROACH:
Climb to 2200 direct ZEYNU and hold.

PHILADELPHIA APP CON 124.35 319.15	CLNC DEL 125.6	UNICOM 123.05 (CTAF) 0
--	--------------------------	----------------------------------

4 NM
055°
235°
ZEYNU

4 NM
RWY06

564 ±
(FAF) ZIXIS
YOSGU
2.4 NM to RWY06

2000
(IF/IAF) DELFA
055°
235°
4 NM

HOLD
6000
2200

MSA RWY06 25 NM
2600

ELEV 435	TDZE 435
----------	----------

4 NM
Holding Pattern

DELFA

2200 ZEYNU

6000
2200

235°
055°

2000

ZIXIS

YOSGU
2.4 NM to RWY06
1 NM to RWY06

3.00°
TCH 45

1240

5 NM
2.4 NM
1.4 NM
1 NM

25 NM
2600

055°

CATEGORY	A	B	C	D
LP MDA	800-1 365 (400-1)			NA
LNAV MDA	820-1	385 (400-1)	820-1 $\frac{1}{8}$ 385 (400-1 $\frac{1}{8}$)	NA
CIRCLING	960-1	525 (600-1)	960-1 $\frac{1}{2}$ 525 (600-1 $\frac{1}{2}$)	NA

MIRL Rwy 6-24 0