



WAAS CH 63112 W23A	APP CRS 230°	Rwy Ldg TDZE Apt Elev	5001 124 125
--	------------------------	-----------------------------	---

RNAV (GPS) RWY 23
BARTOW EXEC (BOW)

RNP APCH. Rwy 23 helicopter visibility reduction below ¼ SM NA. When local altimeter setting not received, use Tampa Intl altimeter setting and increase LPV DA to 560 feet, LNAV/VNAV DA to 681 feet and all MDA 120 feet, increase LPV all Cats visibility ¼ SM, LNAV/VNAV all Cats ½ SM, LNAV Cat C ¼ SM, Cat D ½ SM. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C or above 54°C. VDP and Baro-VNAV NA when using Tampa Intl altimeter setting.	MISSED APPROACH: Climb to 2300 direct FODBI and hold.
---	---

AWOS-3 123.775	TAMPA APP CON 120.65 290.3	BARTOW TOWER ★ 121.2 (CTAF)	GND CON 121.9	UNICOM 122.95
--------------------------	--------------------------------------	--	-------------------------	-------------------------



2300	FODBI	VGSI and RNAV glidepath not coincident (VGSI Angle 3.50/TCH 48).	AKACA	ZOMOV	4 NM Holding Pattern
*LNAV only.	JANGO 2.5 NM to RW23	*1.1 NM to RW23	1800	050° 6000	230° 2200
1.1	1.4	2.5 NM	6.1 NM	GP 3.00°	TCH 60
CATEGORY	A	B	C	D	
LPV DA	454-1 330 (400-1)				
LNAV/VNAV DA	575-1½ 451 (500-1½)				
LNAV MDA	580-1 456 (500-1)		580-1½ 456 (500-1½)	580-1½ 456 (500-1½)	

SE-3, 06 AUG 2026 to 03 SEP 2026

SE-3, 06 AUG 2026 to 03 SEP 2026