

WAAS CH 82143 W18A	APP CRS 177°	Rwy Ldg TDZE Apt Elev	18L 6502 642 643	18R 5003 643 643
--	------------------------	-----------------------------	--	--

RNAV (GPS) RWY 18L

DENTON ENTERPRISE (D'TO)

RNP APCH-GPS.

T


A

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -9°C or above 54°C. For inop ALS, increase LNAV/VNAV all Cats visibility to ¾ SM, and LNAV Cats C and D to 1 SM.

MALSR

MISSED APPROACH: Climb to 1900 then climbing right turn to 4000 direct GREGS and hold.

ATIS 119.325	LONE STAR APP CON 118.1 306.95	DENTON TOWER ★ 119.95 (CTAF) 0	GND CON 123.95
------------------------	--	--	--------------------------



ELEV 643

D TDZE 18L 642
TDZE 18R 643

177°

TWR

1900

4000

GREGS

ZOMLO

BENKS

JIDOS

1 NM to RW18L

2300

177°

357°

6000

3000

GP 3.00°

TCH 50

CATEGORY	A	B	C	D
LPV DA	842-½		200 (200-½)	
LNAV/VNAV DA	950-½		308 (400-½)	
LNAV MDA	1020-½ 378 (400-½)		1020-¾ 378 (400-¾)	
SIDESTEP 18R	1100-1 457 (500-1)		1100-1½ 457 (500-2)	1100-2 457 (500-2)
CIRCLING	1100-1 457 (500-1)	1260-1 617 (700-1)	1380-2 737 (800-2)	1380-2¼ 737 (800-2¼)

MIRL Rwy 18L-36R and 18R-36L 0