

LOC I-PXE <u>109.15</u>	APP CRS 005°	Rwy Ldg TDZE Apt Elev	5004 417 418
-----------------------------------	------------------------	-----------------------------	---

ILS or LOC RWY 36
PERRY-HOUSTON COUNTY (PXE)

	DME or RADAR required
--	-----------------------

▼ Autopilot coupled approach NA below 900. Rwy 36 helicopter visibility reduction below $\frac{3}{4}$ SM NA. Inop table does not apply to S-LS-36. When local altimeter setting not received, use Middle Georgia Rgnl altimeter setting: increase all DA to 705 feet; increase all MDA to 40 feet and Circling visibility Cats C and D $\frac{1}{4}$ SM. For inop ALS, increase S-LOC 36 Cats A/B visibility to 1 SM and Cats C/D to $\frac{1}{8}$ SM. For inop ALS when using Middle Georgia Rgnl altimeter setting, increase S-LS all Cats visibility to $\frac{7}{8}$ SM and S-LOC 36 Cats A/B visibility to 1 SM.


MALSR

MISSED APPROACH: Climb to 1100 then climbing left turn to 2300 on heading 195° and VNA R-291 to SCTRY INT/ RADAR and hold.


AWOS-3
123.825

ATLANTA APP CON★
124.2 279.6

UNICOM
122.725 (CTAF) **L**



ELEV 418		TDZE 417
----------	--	----------



1100
↑

2300
hdg 195°

VNA R-291

SCTR INT

VGSI and ILS glidepath not coincident
(VGSI Angle 3.00/TCH 30).

One Minute Holding Pattern

SCTR INT RADAR

PRDUE INT RADAR

2100

2100

185° → 4000

← 005° 2300

GS 3.00°
TCH 45

5.2 NM

6.7 NM

CATEGORY	A	B	C	D
S-ILS 36	667- ³ / ₄ 250 (300- ³ / ₄)			
S-LOC 36	900- ³ / ₄ 483 (500- ³ / ₄)		900-1 483 (500-1)	
CIRCLING	900-1 482 (500-1)		1140-2 722 (800-2)	1280-2 ³ / ₄ 862 (900-2 ³ / ₄)