



WAAS CH 56316 W30A	APP CRS 301°	Rwy Idg TDZE 99 Apt Elev 99
--	------------------------	---

RNAV (GPS) RWY 30

BREWTON MUNI (12J)

RNP APCH.	Baro-VNAV NA when using Pensacola altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C or above 48°C. Rwy 30 helicopter visibility reduction below ¾ SM NA. When local altimeter setting not received, use Pensacola altimeter setting; increase LPV DA to 611 feet; increase LNAV/VNAV DA to 787 feet; increase all MDAs 100 feet; increase LPV all Cats, LNAV/VNAV all Cats and LNAV Cats C and D visibility ¼ SM. VDP NA when using Pensacola altimeter setting.	MISSED APPROACH: Climb to 2000 direct EHEBA and on track 215° to ODAZO and hold.
-----------	---	--

AWOS-3PT 119.325	PENSACOLA APP CON 127.35 291.625	UNICOM 122.725 (CTAF) 0
----------------------------	--	-----------------------------------



2000	EHEBA	tr 215°	ODAZO	VGSI and RNAV glidepath not coincident (VGSI Angle 3.50/TCH 42).
*LNAV only.		*1.7 NM to RW30		MIEGE YADUC 4 NM Holding Pattern
	RW30			GP 3.00° TCH 37
	1.7 NM	3.5 NM	6.2 NM	
CATEGORY	A	B	C	D
LPV DA	527-1½ 428 (500-1½)			
LNAV/VNAV DA	703-2¼ 604 (700-2¼)			
LNAV MDA	660-1 561 (600-1) 660-1½ 561 (600-1½) 660-1¾ 561 (600-1¾)			