


WAAS CH 90309 W19A	APP CRS 189°	Rwy Ldg TDZE Apt Elev	4500 572 588
--	------------------------	-----------------------------	---


RNAV (GPS) RWY 19
LEBANON MUNI (M54)

RNP APCH - GPS.	For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -16°C or above 54°C. Baro-VNAV and VDP NA when using XNX altimeter setting. Rwy 19 helicopter visibility reduction below ¼ SM NA. Circling NA to Rwy's 4 and 22. When local altimeter setting not received, use XNX altimeter setting: increase LPV DA to 936 feet; increase LNAV/VNAV DA to 1033 feet and all visibilities ½ SM; increase all MDAs 40 feet, LNAV visibility Cat C and D ½ SM, and Circling visibility Cat C ¼ SM.	MISSED APPROACH: Climb to 3000 direct JOGUB and hold.
-----------------	--	--

AWOS-3 118.325	NASHVILLE APP CON 118.4 360.7	UNICOM 122.725 (CTAF)
--------------------------	---	---------------------------------



3000 ↑ JOGUB		LATGE		4 NM Holding Pattern	
		DATMY	2300	009° → ← 189°	6000 3000
RW19		1.5 NM to RW19		189°	2300
1.5 NM		3.9 NM		6 NM	
GP 3.00° TCH 45					
CATEGORY	A	B	C	D	
LPV DA	822-1		250 (300-1)		
LNAV/ VNAV DA	850-1		278 (300-1)		
LNAV MDA	1060-1 488 (500-1)		1060-1 3/8		488 (500-1 3/8)
CIRCLING	1100-1 512 (600-1)	1200-1 612 (700-1)	1440-2 1/2 852 (900-2 1/2)		1520-3 932 (1000-3)



SE-1, 06 AUG 2026 to 03 SEP 2026

SE-1, 06 AUG 2026 to 03 SEP 2026