

(DALL4.TTT) 25331

AL-5936 (FAA)

LANCASTER RGNL (LNC)
LANCASTER, TEXAS

DALLAS FOUR DEPARTURE

LONE STAR DEP CON
125.2 343.65

RADAR and DME required.

NOTE: BELCHER Transition: For aircraft inbound to
the JAN, MLU, and SHV terminal areas only.
NOTE: SOLD0 Transition: ATC assigned.**TOP ALTITUDE:
ASSIGNED BY ATC**BONHAM
114.6 BYP 
Chan 93MAVERICK
113.1 TTT 
Chan 78COBUG
5000
*2300
064°
(38)NOBLY
5000
*2100
064°
(38)TRISS
7500
*2100
074°
(39)

SOLD0

3000
*2300
084°
(36)5000
*2400
094°
(36)

CLARE

9000
*2100
094°
(34)GREGG COUNTY
112.9 GGG 
Chan 76

POTEN

9000
*2100
079°
(44)


TEKBE

5300
*1900
079°
(25)

SHRLY

2400
(25)BELCHER
117.4 EIC 
Chan 121**TAKEOFF MINIMUMS**

Rwy 13: Standard.

Rwy 31: 300-1¼ or standard with a minimum climb
of 210'/NM to 800, or alternatively, with
standard takeoff minimums and a normal
200'/NM climb gradient, takeoff must occur
no later than 1300' prior to DER.

(*CONTINUED ON FOLLOWING PAGE)

NOTE: Chart not to scale.

DALLAS FOUR DEPARTURE
(DALL4.TTT) 27NOV25LANCASTER, TEXAS
LANCASTER RGNL (LNC)

DEPARTURE ROUTE DESCRIPTION	
<u>TAKEOFF RUNWAY 31</u>: Climb on heading 314° to 1800 before turning left. Fly assigned heading for RADAR vectors to appropriate route. Maintain ATC assigned altitude. <u>BELCHER TRANSITION (DALL4.EIC)</u>: From over TTT VOR/DME on TTT R-094 to POTEN, then on EIC R-259 to EIC VORTAC. <u>LITTLE ROCK TRANSITION (DALL4.LIT)</u>: From over TTT VOR/DME on TTT R-064 to ORTRO, then on LIT R-237 to LIT VORTAC. <u>SOLDO TRANSITION (DALL4.SOLD)</u>: From over TTT VOR/DME on TTT R-084 to SOLD. <u>TEXARKANA TRANSITION (DALL4.TXK)</u>: From over TTT VOR/DME on TTT R-074 to SHERO, then on TXK R-244 to TXK VORTAC.	

SC-2, 06 AUG 2026 to 03 SEP 2026

SC-2, 06 AUG 2026 to 03 SEP 2026