


WAAS CH 78136 W28A	APP CRS 279°	Rwy Ldg TDZE Apt Elev	3950 153 153
--	------------------------	-----------------------------	---

RNAV (GPS) RWY 28
PLANT CITY (PCM)


Baro-VNAV NA when using Lakeland altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C (5°F) or above 54°C (130°F). DME/DME RNP-0.3 NA. Night landing: Rwy 28 NA. Helicopter visibility reduction below 1 SM NA. When local altimeter setting not received use Lakeland altimeter setting and increase all DA/MDA 20 feet.

MISSED APPROACH:
Climb to 2000 direct
UJURO and hold.

AWOS-3 120.025	TAMPA APP CON 120.65 290.3	CLNC DEL 121.725 (GCO)	UNICOM 123.05 (CTAF)
--------------------------	--------------------------------------	----------------------------------	--------------------------------



ELEV 153	TDZE 153
-----------------	-----------------



2000 UJURO		VGSi and RNAV glidepath not coincident (VGSi Angle 3.00/TCH 36).		4 NM Holding Pattern	
		GP 3.50° TCH 57			
CATEGORY	A	B	C	D	
LPV DA	414-1	261 (300-1)	NA	NA	
LNAV/VNAV DA	459-1	306 (400-1)	NA	NA	
LNAV MDA	600-1	447 (500-1)	NA	NA	
CIRCLING	680-1 527 (600-1)	720-1 567 (600-1)	NA	NA	