

APP CRS
134°

Rwy Ldg
TDZE
46

Apt Elev
46

RNAV (GPS) RWY 13

HAMMOND NORTHSORE RGNL (HDC)

RNP APCH - GPS.

▼

⚠

Rwy 13 helicopter visibility reduction below ¼ SM NA. VDP NA when using Louis Armstrong New Orleans Intl altimeter setting. When local altimeter setting not received, use Louis Armstrong New Orleans Intl altimeter setting and increase all MDAs 100 feet and LNAV visibility Cat C/D ¼ SM, and Circling visibility Cat C/D ½ SM.

MISSED APPROACH:
Climb to 2000 direct COBIM and hold.

ATIS 118.325	NEW ORLEANS APP CON 119.3 350.35	HAMMOND TOWER ★ 120.575 (CTAF) 0	GND CON 119.85
------------------------	--	--	--------------------------

HEVOT

2000

134°

ZOPAD

1600

3.30° TCH 50

ADAPPE 2.8 NM to RW13

540

1 NM to RW13

RW13

2000 COBIM

6 NM

1.5 NM

1.8 NM

1 NM

CATEGORY	A	B	C	D
LNAV MDA	440-1	394 (400-1)	440-1½	394 (400-1½)
CIRCLING	500-1	454 (500-1)	620-1½ 574 (600-1½)	920-2¾ 874 (900-2¾)

ELEV 46

TDZE 46

134°

81

5001 X 150

6502 X 100

36

TWR

REIL Rwy 13, 31 and 36

MIRL Rwy 13-31 and 18-36

HAMMOND, LOUISIANA

Orig 20APR23

30°31'N-90°25'W

RNAV (GPS) RWY 13

HAMMOND NORTHSORE RGNL (HDC)

SC-4, 06 AUG 2026 to 03 SEP 2026