

WAAS CH 45747 W05A	APP CRS 040°	Rwy Ldg TDZE 980 Apt Elev 980
--	------------------------	---

RNAV (GPS) RWY 5

FAYETTE COUNTY (I23)

RNP APCH - GPS.


▼

⚠

Rwy 5 helicopter visibility reduction below ¾ SM NA. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -16°C or above 54°C. Baro-VNAV and VDP NA when using I66 altimeter setting. Circling Rwy 23 NA at night. When local altimeter setting not received, use I66 altimeter setting and increase LPV DA to 1287 feet; increase LNAV/VNAV DA to 1597 feet and all visibilities ½ SM. Increase all MDAs 60 feet and LNAV visibility Cat C/D ½ SM, and Circling visibility Cat C ¼ SM.

MISSED APPROACH: Climb to 3000 direct AMINO and hold.

AWOS-3PT 132.1	COLUMBUS APP CON 134.0 279.6	UNICOM 122.8 (CTAF) 0
--------------------------	--	---------------------------------



4 NM Holding Pattern HOPKN

6000 ← 240° 3000 → 060°

GP 3.00° TCH 55

WAKLI 3000 060°

MABLV 2600 040°

1.6 NM to RW05

RW05

5 NM 3.1 NM 3.3 NM 1.6 NM

CATEGORY	A	B	C	D
LPV DA	1230-1 250 (300-1)			
LNAV/VNAV DA	1540-1½ 560 (600-1½)			
LNAV MDA	1540-1 560 (600-1)	1540-1½ 560 (600-1½)		
CIRCLING	1540-1 560 (600-1)	1600-1 620 (700-1)	1600-1¾ 620 (700-1¾)	1660-2¼ 680 (700-2¼)

ELEV 980 TDZE 980

3000 AMINO

REIL Rwy 23 0 MRL Rwy 5-23 0