

WAAS CH 82204 W18A	APP CRS 181°	Rwy Ldg TDZE 999 Apt Elev 1004
--	------------------------	--


RNAV (GPS) RWY 18

KANSAS CITY/LEE'S SUMMIT RGNL (LXT)

⚠ For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -17°C (2°F) or above 54°C (130°F).
Rwy 18 helicopter visibility reduction below ¾ SM NA. DME/DME RNP-0.3 NA. Baro-VNAV and VDP NA when using Kansas City Downtown/Wheeler Fld altimeter setting. When local altimeter setting not received, use Kansas City Downtown/Wheeler Fld altimeter setting: increase LPV DA to 1317 feet and all visibilities ½ SM; increase LNAV/VNAV DA to 1434 feet and all visibilities ¼ SM; increase all MDA 80 feet and LNAV visibility Cat C and D ¾ SM, Circling Cats C and D ¼ SM.

MISSED APPROACH:
Climb to 3000 direct WOMPO and hold.

ASOS 124.175	KANSAS CITY APP CON 118.4 307.35	UNICOM 122.8 (CTAF) 0
------------------------	--	---------------------------------



3000 WOMPO		KISNE		SOXOE	
*LNAV only		*1 NM to RWY 18		4 NM Holding Pattern	
RWY 18		2600		001° → 3000	
1 NM		3.9 NM		GP 3.00° TCH 44	
CATEGORY		A		B	
LPV DA		1249-¾		250 (300-¾)	
LNAV/VNAV DA		1366-1		367 (400-1)	
LNAV MDA		1360-1		361 (400-1)	
CIRCLING		1440-1 436 (500-1)		1780-2¼ 776 (800-2¼)	

