


WAAS CH 82433 W06A	APP CRS 062°	Rwy Ldg 4106 TDZE 1079 Apt Elev 1084
--	------------------------	---

RNAV (GPS) RWY 6

SMITHVILLE MUNI (ØA3)

RNP APCH.	Baro-VNAV NA. Procedure NA at night. Rwy 6 helicopter visibility reduction below 1 SM NA. Use Sparta altimeter setting; when not received, use Tullahoma altimeter setting and increase LPV DA to 1486 feet and all visibilities ⅓ SM, increase LNAV/VNAV DA to 1645 feet and all visibilities ¼ SM, increase all MDA 60 feet and LNAV visibility Cat C ¼ SM.	MISSED APPROACH: Climb to 3800 direct ERAPE and hold.
-----------	---	---

SRB AWOS-3 128.25	MEMPHIS CENTER 128.15 323.125	UNICOM 122.8 (CTAF)
-----------------------------	---	-------------------------------



4 NM Holding Pattern		VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 28).		3800	ERAPE
3800 ← 242°		062° →		3100	UWOYO 3 NM to RW06
GP 3.00° TCH 53		3100		2080	RW06
7 NM		3.2 NM		3 NM	
CATEGORY	A	B	C	D	
LPV DA	1433-1 354 (400-1)			NA	
LNAV/VNAV DA	1592-1 513 (600-1 ⅓)			NA	
LNAV MDA	1580-1 501 (500-1)			1580-1 501 (500-1 ⅓)	NA

