



WAAS CH 40335 W22A	APP CRS 220°	Rwy Ldg 5000 TDZE 615 Apt Elev 615
--	------------------------	---

RNAV (GPS) RWY 22
SILER CITY MUNI (SCR)

⚠ For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -16°C (4°F) or above 54°C (130°F). DME/DME RNP-0.3 NA. Procedure NA at night. Baro-VNAV NA when using Asheville altimeter setting. Rwy 4, 22 helicopter visibility reduction below 1 SM NA. When local altimeter setting not received, use Asheville altimeter setting: increase all DA 53 feet and all MDA 60 feet; increase LPV all Cats, LNAV/VNAV all Cats, and LNAV Cat C visibilities 1/8 mile, increase Circling Cat C visibility 1/4 mile.

MISSED APPROACH:
Climb to 3000 direct COTEN and hold.

AWOS-3 125.775	GREENSBORO APP CON 126.6 327.075	UNICOM 122.7 (CTAF) 0
--------------------------	--	---------------------------------



3000 COTEN

VGSI and RNAV glidepath not coincident (VGSI Angle 3.50/TCH 45).

4 NM Holding Pattern

OPUXY

IPSIQ 2300

220°

040° → 3000

← 220°

2300

RW22

4.4 NM

6 NM

GP 3.50° TCH 40

CATEGORY	A	B	C	D
LPV DA	954-1	339 (400-1)		NA
LNAV/VNAV DA	1140-1 ⁵ / ₈	525 (600-1 ⁵ / ₈)		NA
LNAV MDA	1160-1	545 (600-1)	1160-1 ⁵ / ₈ 545 (600-1 ⁵ / ₈)	NA
CIRCLING	1240-1	625 (700-1)	1240-1 ³ / ₄ 625 (700-1 ³ / ₄)	NA

SE-2, 06 AUG 2026 to 03 SEP 2026

SE-2, 06 AUG 2026 to 03 SEP 2026