


ILS or LOC RWY 27
COBB COUNTY INTL/MCCOLLUM FLD (RYY)

MISSED APPROACH: Climb to 1600 then climbing right turn to 3500 on heading 300° and on RMG VORTAC R-108 to TIPPY/RMG 11 DME and hold.



SE-4, 06 AUG 2026 to 03 SEP 2026

The diagram illustrates the CUMAV FIX and associated navigation data. It shows a flight path starting from the bottom left, passing through the CUMAV I-RYY (2.9) fix, and continuing towards the 3500 altitude. Key data points include:

- Altitudes:** 1600, 3500, 1620, 3000, 3000, 3500.
- Distances:** 1.8 NM, 4.3 NM, 6.7 NM.
- Angles:** 273°.
- Navigation Aids:** I-RYY (1.1), CUMAV I-RYY (2.9), ALBRS I-RYY (7.2) RADAR, OVPEW I-RYY (13.9) RADAR.
- Speed:** GS 3.00° TCH 46.

CATEGORY	A	B	C	D
S-ILS 27	1211-¾ 200 (200-¾)			
S-LOC 27	1620-¾	609 (600-¾)	1620-1½	609 (600-1½)
CIRCLING	1800-1	760 (800-1)	2180-3	1140 (1200-3)
CUMAV FIX MINIMUMS				
S-LOC 27	1480-¾	469 (500-¾)	1480-1½	469 (500-1½)
CIRCLING	1800-1	760 (800-1)	2180-3	1140 (1200-3)

Diagram illustrating the HIRL Rwy 9-27 layout and navigation aids:

- Star symbol (☆) at the start of the runway.
- Circle with a cross (⊗) at the 6295 X 100 intersection.
- Square symbol (■) for the TWR (Tower).
- Circle with a cross (⊗) at the 0.7% UP intersection.
- Circle with a cross (⊗) at the 27° intersection.
- Bearing of 273° indicated by an arrow pointing towards the runway end.