

LOC/DME	I-EYK	APP CRS	Rwy Ldg
111.7		048°	5500
Chan 54			TDZE 18
			Apt Elev 19

ILS or LOC RWY 5

CHESAPEAKE RGNL (CPK)

When local altimeter setting not received, use ORF altimeter setting and increase DA to 256 feet; increase all MDAs 40 feet and CEKAD fix minimums S-LOC 5 visibility Cats C and D 1/2 SM. For inop ALS, increase S-LOC 5 Cats C and D visibility to 1 3/8 SM.

MALSR

MISSED APPROACH: Climb to 500 then climbing left turn to 2000 on heading 190° and ORF VORTAC R-216 to NALDE INT/I-EYK 12.3 DME and hold.

AWOS-3 123.675	NORFOLK APP CON 118.9 353.7	GCO 135.075	UNICOM 123.075 (CTAF) 0
-------------------	--------------------------------	----------------	----------------------------

LOCALIZER 111.7
I-EYK
Chan 54

142±
CEKAD
I-EYK 2.6

TAVAE INT
I-EYK 6.2

(IF/IAF)
NALDE INT
I-EYK 12.3

2000 NoPT
R-324
Chan 104 (Y)

Procedure NA for arrival on ECG
VOR/DME airway radials 265 CW 311.

IAF
ELIZABETH CITY
115.75 ECG
Chan 104 (Y)

MSA ORF 2.5 NM
1800
2300

ELEV 19 TDZE 18

One Minute Holding Pattern

500

2000

hdg 190°

ORF R-216

NALDE INT

NALDE INT
I-EYK 12.3

TAVAE INT
I-EYK 6.2

CEKAD
I-EYK 2.6

I-EYK 1.1

4000

2000

←228°

048°→

048°

1700

*480

6.1 NM

3.7 NM

1.5 NM

GS 3.00°

TCH 43

*520 when using ORF altimeter setting.

CATEGORY	A	B	C	D
S-ILS 5		218-1/2	200 (200-1/2)	
S-LOC 5	480-1/2	462 (500-1/2)	480-1	462 (500-1)
CIRCLING	480-1	461 (500-1)	520-1 1/2 501 (600-1 1/2)	580-2 561 (600-2)
CEKAD FIX MINIMUMS				
S-LOC 5	400-1/2	382 (400-1/2)	400-5/8	382 (400-5/8)
CIRCLING	460-1 441 (500-1)	480-1 461 (500-1)	520-1 1/2 501 (600-1 1/2)	580-2 561 (600-2)

500 X 100

HIRL Rwy 5-23

REIL Rwy 23

048°

NORFOLK, VIRGINIA

Amtd 2 27NOV25

36°40'N-76°19'W

CHESAPEAKE RGNL (CPK)

ILS or LOC RWY 5