

LOC/DME I-JNX 111.15 Chan 48 (Y)	APP CRS 032°	Rwy Ldg 5500 TDZE 147 Apt Elev 164	ILS Z or LOC Z RWY 3 JOHNSTON RGNL (JNX)
--	------------------------	---	---

ADF required. DME or RADAR required for LOC only.

▼



▲ NA

Rwy 3 helicopter visibility reduction below ¾ SM NA. Inop table does not apply to S-ILS 3. For inop ALS, increase S-LOC 3 Cats C/D visibility to 2½ ; increase S-LOC 3 JONIR Fix Minimums Cats C and D to 1¾ SM. When local altimeter setting not received, use HRJ altimeter setting and increase S-ILS 3 DA to 447 feet; increase all MDAs 60 feet and Circling visibility Cat A/C ¼ SM.
*1000 when using HRJ altimeter setting.

MALSR

MISSED APPROACH: Climb to 1000 then climbing right turn to 1800 direct JN NDB and hold, continue climb-in-hold to 1800.

AWOS-3 120.225	RALEIGH APP CON 125.3 353.675	GCO 135.075	UNICOM 122.725 (CTAF) 0
--------------------------	---	-----------------------	--



CATEGORY	A	B	C	D
S-ILS 3		397-1	250 (300-1)	
S-LOC 3*	940-1	793 (800-1)	940-1¾	793 (800-1¾)
CIRCLING	940-1 776 (800-1)	940-1¼ 776 (800-1¼)	960-2½ 796 (800-2½)	1100-3 936 (1000-3)
JONIR DME FIX MINIMUMS				
S-LOC 3	780-1	633 (700-1)	780-1⅔	633 (700-1⅔)
CIRCLING	780-1	616 (700-1)	960-2¼ 796 (800-2¼)	1100-3 936 (1000-3)

MIRL Rwy 3-21

REIL Rwy 21

FAF to MAP 4.1 NM

Knots	60	90	120	150	180
Min:Sec	4:06	2:44	2:03	1:38	1:22