

▼

▲

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -8°C (18°F) or above 54°C (130°F). When local altimeter setting not received, use Dallas Love Fld altimeter setting and increase all DA 70 feet and all MDA 80 feet, and increase LNAV/VNAV all Cats visibility ½ mile, LNAV Cat C/D and Circling Cat C/D visibility ¼ mile.
DME/DME RNP-0.3 NA. VDP and Baro-VNAV NA when using Dallas Love Fld altimeter setting. For inop MALS increase LNAV/VNAV all Cats visibility to ¾ mile and LNAV Cat D visibility to 1 mile. For inop MALS when using Dallas Love Fld altimeter setting increase LPV all Cats visibility to ¾ mile, LNAV/VNAV Cat D visibility to 1½ mile, and LNAV Cat D visibility to 1¼ mile. Inop table does not apply to LPV all Cats.

MALS

A4

≡

MISSED APPROACH:

Climb to 3000 direct VELCI and hold.

ATIS 119.925	LONE STAR APP CON 124.3 282.275	MCKINNEY TOWER ★ 118.825 (CTAF) 0	GND CON 121.875	CLNC DEL 121.35 (When twr closed)	UNICOM 122.95
-----------------	------------------------------------	--------------------------------------	--------------------	---	------------------

