

CHARLOTTE DEP CON  
128.325 307.8  
AWOS-3  
128.175  
CLNC DEL  
121.75 254.375  
GND CON  
121.75 254.375  
STANLY COUNTY TOWER ★  
126.275 (CTAF) 291.9

RNAV 1 - DME/DME/IRU or GPS.

RADAR required.

TOP ALTITUDE:  
3000

TAKEOFF MINIMUMS  
Rwys 4L, 22R: NA - Environmental.  
Rwy 22L: Standard.  
Rwy 4R: 300-1¾ or standard with  
minimum climb of 315'/NM to 1000.

LAMDE

LILLS

NOTE: Turbojet only.  
NOTE: Transponder code will be issued via PDC  
or CLT CLNC DEL.  
NOTE: If unable to accept climb rates, advise ATC  
on initial contact.  
NOTE: Upon reaching 10000 MSL, accelerate to  
and maintain 280K, if unable advise ATC.

MSA VUJ 25 NM

3100

NOTE: Chart not to scale.

DEPARTURE ROUTE DESCRIPTION

Climb on heading assigned by ATC for RADAR vectors to LAMDE, then on depicted route to LILLS. Maintain 3000. Expect filed altitude 10 minutes after departure.

SE-2, 06 AUG 2026 to 03 SEP 2026

SE-2, 06 AUG 2026 to 03 SEP 2026