

WAAS CH 72823 W36A	APP CRS 359°	Rwy Idg TDZE 1115 Apt Elev 1115	4001 1115 1115
--	------------------------	---	---

RNAV (GPS) RWY 36


OSCEOLA MUNI (I75)

⚠

When VGSI inop, Circling Rwy 18 NA at night. Baro-VNAV NA when using Chariton altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -17°C (2°F) or above 54°C (130°F). DME/DME RNP-0.3 NA. VDP NA with Chariton altimeter setting. When local altimeter setting not received, use Chariton altimeter setting and increase all DA 44 feet and all MDA 60 feet. Increase LPV all Cats visibility to 1 mile and LNAV/VNAV all Cats visibility to 1¼ mile. Visibility reduction by helicopters NA.

MISSED APPROACH:
Climb to 3000 direct JAXWU and hold.

AWOS-3 120.975	DES MOINES APP CON 123.9 360.7	UNICOM 122.8 (CTAF) 0
--------------------------	--	---------------------------------



MSA RW36 25 NM
2900

LAMONI LMN

Procedure NA for arrivals on LMN VOR/DME airway radials 009 CW 106.

4 NM Holding Pattern

GP 3.00° TCH 40

5.1 NM, 2.9 NM, 0.8, 1.2

VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 31).

*1780

*1.2 NM to RW36

*LNAV only.

CATEGORY	A	B	C	D
LPV DA	1365-7/8	250 (300-7/8)		NA
LNAV/VNAV DA	1423-1	308 (400-1)		NA
LNAV MDA	1540-1	425 (500-1)		NA
CIRCLING	1580-1	465 (500-1)		NA

ELEV 1115 | TDZE 1115

REIL Rwy 18 and 36 0

MIRL Rwy 18-36 0

81 400 X 75

36 359°

NC-3, 06 AUG 2026 to 03 SEP 2026

NC-3, 06 AUG 2026 to 03 SEP 2026