

RNP APCH.


▼

▲

Procedure NA at night. Baro-VNAV and VDP NA when using Kipnuk altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -21°C or above 54°C. When local altimeter setting not received, use Kipnuk altimeter setting and increase all DA and MDA 160 feet; increase LPV all Cats visibility and LNAV/VNAV all Cats visibility ¼ SM, LNAV Cats C, D visibility ⅜ SM, increase Circling Cat C visibility ½ SM, increase Circling Cat D visibility ¼ SM.

MISSED APPROACH: Climb to 5200 direct CUTEB and hold, continue climb-in-hold to 5200.

AWOS-3P 121.575	ANCHORAGE CENTER 125.2 372.0	KENAI RADIO 122.1	CTAF 122.8
---------------------------	--	-----------------------------	----------------------



4 NM Holding Pattern		HOTKU		JOSAD		5200 ↑ CUTEB	
6000 ← 303° 2500 → 123°		123° 1600		*LNAV only.		123°	
GP 3.00° TCH 35		5.9 NM		3.4 NM		1.4 NM to RW12	
CATEGORY		A		B		C	
LPV DA		292-1		250 (300-1)		RW12	
LNAV/VNAV DA		292-1		250 (300-1)		4000 X 75	
LNAV MDA		500-1 458 (500-1)		500-1 3/8 458 (500-1 3/8)		30	
CIRCLING		500-1 458 (500-1)		580-1 1/2 538 (600-1 1/2)		600-2 558 (600-2)	
						MIRL Rwy 12-30	