

WAAS CH 63017 W16A	APP CRS 162°	Rwy Ldg 10000 TDZE 69 Apt Elev 69
--	------------------------	--

RNAV (GPS) RWY 16

NORTHWEST FLORIDA BEACHES INTL (ECP)

⚠

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C (5°F) or above 54°C (130°F). DME/DME RNP-0.3 NA. When local altimeter setting not received, use Destin altimeter setting and increase all DA 88 feet, increase all MDA 100 feet, and increase LNAV/VNAV all Cats visibility and LNAV Cat C and D visibility ¾ mile. Baro-VNAV and VDP NA when using Destin altimeter setting. For inop MALSR, increase LNAV Cat C and D visibility to 1 mile. For inop MALSR when using Destin altimeter setting, increase all LPV visibility to ¾ mile, increase all LNAV/VNAV visibility to 1¾ mile, and increase LNAV Cat C and D visibility to 1¾ mile.

MALSR

MISSED APPROACH: Climb to 500 then climbing left turn to 4000 direct SCARE and hold, continue climb-in-hold to 4000.

ATIS 119.975	TYNDALL APP CON★ 125.2	PANAMA CITY TOWER★ 118.95 (CTAF) 0	GND CON 121.65
------------------------	----------------------------------	--	--------------------------

ELEV 69	TDZE 69
162° 9L 1000 X 150 TWR★ 3A	
TDZ/CL Rwy 16 0 HIRL Rwy 16-34 0 REIL Rwy 34 0	

PANAMA CITY, FLORIDA
Amdt 2A 29MAY14

30°22'N-85°48'W

NORTHWEST FLORIDA BEACHES INTL (ECP)
RNAV (GPS) RWY 16