

LOC/DME I-ABI 110.3 Chan 40	APP CRS 355°	Rwy Ldg 7198 TDZE 1776 Apt Elev 1791
---	------------------------	---

ILS or LOC RWY 35R
ABILENE RGNL (ABI)

▼ VDP NA when using DYS altimeter setting. For inop ALS, increase S-ILS 35R Cat E visibility to RVR 4000, and S-LOC 35R Cat C/D/E visibility to 1 3⁄8 SM.

▲ When local altimeter setting not received, use DYS altimeter setting and increase S-ILS 35R DA to 1997 feet; increase all MDAs 40 feet and S-LOC 35R visibility Cat C/D/E 1⁄8 SM, and Circling visibility Cat D 1⁄4 SM.



* RVR 1800 authorized with use of FD or AP or HUD to DA.


* RVR 1800 NA when using DYS altimeter setting.

MALSR

MISSED APPROACH: Climb to 3300 then climbing left turn to 5000 direct ABI VORTAC and hold, continue climb-in-hold to 5000.

ATIS 118.25	ABILENE APP CON 125.0 338.3 (E) 127.2 282.3 (W)	ABILENE TOWER 120.1 257.8	GND CON 121.7 348.6
-----------------------	---	-------------------------------------	-------------------------------



3300	5000	ABI	One Minute Holding Pattern				
							
							
CATEGORY	A	B	C	D	E		
S-ILS 35R *	1976/24 200 (200-½)						
S-LOC 35R	2360/24	584 (600-½)	2360-1¼ 584 (600-1¼)				
CIRCLING	2360-1	569 (600-1)	2420-1¾ 629 (700-1¾)	2460-2 669 (700-2)	2620-3 829 (900-3)		