



WAAS CH 56599 W31A	APP CRS 311°	Rwy Ldg 8794 TDZE 1645 Apt Elev 1661
--	------------------------	---

RNAV (GPS) RWY 31

BISMARCK MUNI (BIS)

RNP APCH - GPS.		MALSR	MISSED APPROACH: Climb to 3800 direct WIMTO and hold.	
For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -18°C or above 54°C. Inop table does not apply to LNAV/VNAV. *RVR 1800 authorized with use of FD or AP or HUD to DA.				
ATIS 119.35	BISMARCK APP CON* 126.3 298.9	BISMARCK TOWER* 118.3(CTAF) 0 257.8	GND CON 121.9	UNICOM 122.95



3800

↑

WIMTO

✳

4 NM

Holding Pattern

JUMGU

131° →

← 311°

3700

GP 3.00°

TCH 48

CUCAY

2 NM to RW31

ICONO

3500

311°

3500

2320

2 NM

3.7 NM

6.3 NM

RW31

↶

CATEGORY	A	B	C	D
LPV DA*	1845/24 200 (200-½)			
LNAV/VNAV DA	2269-1¾ 624 (700-1¾)			
LNAV MDA	2180/24 535 (600-½)		2180/55 535 (600-1)	
CIRCLING	2200-1 539 (600-1)		2460-2¼ 799 (800-2¼)	2460-2½ 799 (800-2½)