


WAAS CH 56204 W06A	APP CRS 058°	Rwy Ldg TDZE 773 Apt Elev 799
--	------------------------	---

RNAV (GPS) Y RWY 6L
CLEVELAND-HOPKINS INTL (CLE)

RNP APCH. ▼ For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -18°C (0°F) or above 54°C (130°F). Circling Rwy 10 NA at night. For inop ALS, increase LNAV/VNAV all Cats visibility to RVR 5500 and increase LNAV Cats C/D visibility to 1¾ SM.	ALSF-2 ⓐ	MISSED APPROACH: Climb to 3000 direct ACAPO and on track 001° to PASLE and hold.
---	-------------	--

D-ATIS 127.85	CLEVELAND APP CON 126.55 346.325	CLEVELAND TOWER 124.5 273.45	GND CON 121.7 273.45
-------------------------	--	--	--------------------------------



VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 69).				3000	ACAPO	PASLE
BETLL				↑	✧	tr 001°
2900				2000	2000	
GP 3.00° TCH 55				*LNAV only.		
1.9 NM				*1.3 NM to RWY 06L		
1.1 NM				RWY 06L		
2.4 NM						
1.3 NM						
CATEGORY	A	B	C	D		
LPV DA	973/18			200 (200-½)		
LNAV/VNAV DA	1120/30			347 (400-⅝)		
LNAV MDA	1260/24	487 (500-½)	1260/50	487 (500-1)		
CIRCLING	1420-1	621 (700-1)	1420-1¾ 621 (700-1¾)	1420-2 621 (700-2)		

