

WAAS CH 78244 W22A	APP CRS 222°	Rwy Ldg TDZE 3950 Apt Elev 3962
--	------------------------	---

RNAV (GPS) Y RWY 22

EL PASO INTL (ELP)

RNP APCH - GPS.

▼


ASR

Circling NA for Cat D north of Rwy 26R and northwest of Rwy 4. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -5°C or above 54°C. For inop ALS increase LNAV/VNAV Cats A/B/C visibility to RVR 4000, Cat D visibility to RVR 4500 and LNAV Cat C/D visibility to RVR 5500.


MALSR

MISSED APPROACH: Climb to 4600 then climbing left turn to 8000 direct GIFEN and hold, continue climb-in-hold to 8000.

D-ATIS 120.0 254.3	EL PASO APP CON 124.25 298.85	EL PASO TOWER 118.3 239.275	GND CON 121.9 348.6
------------------------------	---	---------------------------------------	-------------------------------



4600 8000 GIFEN	VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 70).			
↑	↶	△	PRISO 6800 222° 5900 5100 5100 0.9 NM to RWY 22 0.9 2.6 NM 3.4 NM 5.1 NM GP 3.00° TCH 55	
CATEGORY	A	B	C	D
LPV DA	4150/24 200 (200-½)			
LNAV/VNAV DA	4200/24 250 (300-½)			4221/24 271 (300-½)
LNAV MDA	4300/24	350 (400-½)	4300/30	350 (400-½)
CIRCLING	4420-1 458 (500-1)	4440-1 478 (500-1)	4480-1½ 518 (600-1½)	4680-2¼ 718 (800-2¼)



SC-3, 03 SEP 2026 to 01 OCT 2026

SC-3, 03 SEP 2026 to 01 OCT 2026