

MIAMI, FLORIDA

AL-257 (FAA)

25275

WAAS CH 40205 W27A	APP CRS 272°	Rwy Ldg 12755 TDZE 9 Apt Elev 9
--	------------------------	--

RNAV (GPS) Y RWY 27

MIAMI INTL (MIA)

RNP APCH-GPS.





Simultaneous approach authorized. LNAV procedure NA during simultaneous operations. Use of FD or AP required during simultaneous operations. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below 8°C or above 54°C. *RVR 1800 authorized with use of FD or AP or HUD to DA.

MALSR



MISSED APPROACH: Climb to 800 then climbing right turn to 4000 direct BRBRA and hold, continue climb-in-hold to 4000.

D-ATIS 119.15	MIAMI APP CON 124.85 322.3	MIAMI TOWER 118.3 256.9	121.8 (8L/8R/12/26L/26R) 127.5 (9/27/30)	348.6
-------------------------	--------------------------------------	-----------------------------------	---	--------------



800	4000	BRBRA	VGSi and RNAV glidepath not coincident (VGSi Angle 3.00°/TCH 71°).		HENDN
1.5 NM		3.9 NM to RW27	1800	3000	4000
1.5 NM		2.4 NM	1.6 NM	3.8 NM	3.2 NM
CATEGORY		A	B	C	D
LPV DA*		209/24		200 (200-½)	
LNAV/VNAV DA		439/40		430 (500-¾)	
LNAV MDA		560/24	551 (600-½)	560/60	551 (600-¼)

MIAMI, FLORIDA
Amdt 4 12AUG21

25°48'N-80°17'W

MIAMI INTL (MIA)

RNAV (GPS) Y RWY 27

SE-3, 03 SEP 2026 to 01 OCT 2026

SE-3, 03 SEP 2026 to 01 OCT 2026