


APP CRS	Rwy Ldg	12000
087°	TDZE	21
	Apt Elev	36

RNAV (RNP) Z RWY 9R


PHILADELPHIA INTL (PHL)

RNP AR APCH - GPS.	ALSIF-2	MISSED APPROACH: Climb to 3000 on track 087° to ASGEW and on track 169° to CIPOK, and on track 259° to OOD VORTAC and hold.
▼ For uncompensated Baro-VNAV systems, procedure NA below -12°C or above 54°C. For inop ALS, increase RNP 0.16 all Cats visibility to RVR 4500 and RNP 0.30 all Cats visibility to 1½ SM.		

D-ATIS	PHILADELPHIA APP CON	PHILADELPHIA TOWER	GND CON
133.4	124.35 319.15	118.5 327.05 (08/26, 09L/27R, 17/35) 135.1 327.05 (09R/27L)	121.9 348.6



	CHETM	ANDHW	RW09R	OOD
	3000	1500	327.05	327.05
	072°	087°	087°	259°
	GP 3.00°			
	TCH 58			
	5 NM	4.4 NM		
CATEGORY	A	B	C	D
RNP 0.16 DA		424/40	403 (400-¾)	
RNP 0.30 DA		461/50	440 (500-1)	



AUTHORIZATION REQUIRED