

|                                        |                        |                                                     |
|----------------------------------------|------------------------|-----------------------------------------------------|
| WAAS<br>CH <b>82211</b><br><b>W25B</b> | APP CRS<br><b>258°</b> | Rwy Ldg<br>TDZE <b>1126</b><br>Apt Elev <b>1135</b> |
|----------------------------------------|------------------------|-----------------------------------------------------|

RNAV (GPS) Y RWY 25L

PHOENIX SKY HARBOR INTL (PHX)

RNP APCH-GPS.

Simultaneous approach authorized. LNAV procedure NA during simultaneous operations. Use of FD or AP required during simultaneous operations. For uncompensated Baro-VNAV systems, procedure NA below 2°C or above 54°C. For inop ALS, increase visibility LPV all Cats to 1 SM, LNAV/VNAV all Cats to 1½ SM and LNAV Cats C/D 1¾ SM.

MALSR

MISSED APPROACH: Climb to 1900 then climbing left turn to 5000 direct CHOCK and on track 145° to BRAAK and hold.

|                          |                                        |                                                                                   |                                                               |
|--------------------------|----------------------------------------|-----------------------------------------------------------------------------------|---------------------------------------------------------------|
| D-ATIS<br><b>127.575</b> | PHOENIX APP CON<br><b>128.65 353.9</b> | PHOENIX TOWER<br><b>118.7 278.8</b> (8-26)<br><b>120.9 254.3</b> (7L-25R, 7R-25L) | GND CON<br><b>119.75 269.2</b> (N)<br><b>132.55 269.2</b> (S) |
|--------------------------|----------------------------------------|-----------------------------------------------------------------------------------|---------------------------------------------------------------|

MISSED APCH FIX

ELEV 1135

D

TDZE 1126

1900

5000

CHOCK

tr 145°

BRAAK

TEKUY 2.4 NM to RW25L

TIPLE 3000

GIPSE 4000

HAMEK 5000

GP 3.00° TCH 49

| CATEGORY     | A                  | B | C                     | D                    |
|--------------|--------------------|---|-----------------------|----------------------|
| LPV DA       | 1449-½ 323 (400-½) |   |                       |                      |
| LNAV/VNAV DA | 1589-1 463 (500-1) |   |                       | 1674-1⅛ 548 (600-1⅛) |
| LNAV MDA     | 1740-½ 614 (700-½) |   | 1740-1⅜ 614 (700-1⅜)  |                      |
| CIRCLING     | 1740-1 605 (700-1) |   | 2040-2¾ 905 (1000-2¾) | 2340-3 1205 (1300-3) |

HIRL Rwy 8-26, 7L-25R and 7R-25L  
REIL Rwy 26

PHOENIX, ARIZONA  
Amdt 2 19MAY22

PHOENIX SKY HARBOR INTL (PHX)

33°26'N-112°01'W

RNAV (GPS) Y RWY 25L