

LOC/DME I-SZK

111.1

Chan **48**

APP CRS

072°

Rwy Idg

6800

TDZE

1175

Apt Elev

1175

LDA Y RWY 6

ROANOKE/BLACKSBURG RGNL (WOODRUM FLD) (R.O.A.)

RADAR required for procedure entry. ADF required.
DME or RADAR required for LOC only.

▼

For inop ALS, increase S-LDA 6 visibility Cats A/B to 1 3/8 SM.
Circling NA northwest of Rwy 6-24. Inop table does not apply to S-LDA 6 Cats C and D. Inop table does not apply to S-LDA/GS 6 all Cats.

❄-12° C

MALSRL

MISSED APPROACH: Climb to 2200 then climbing right turn to 5000 direct VIT NDB and hold, continue climb-in-hold to 5000.

ATIS

132.375

ROANOKE APP CON

133.225 339.8

ROANOKE TOWER

118.3 257.8

GND CON

121.9 257.8

LDA/GLIDE SLOPE

One Minute Holding Pattern

VGSI and LDA glidepath not coincident (VGSI Angle 3.00/TCH 58).

2200 5000 VIT

EXUNE I-SZK 15.4

SAGEY I-SZK 12.7

RAMKE I-SZK 9.9

SKIRT OM I-SZK 4.9

JOKNI I-SZK 1.4

5600 5300

GS 3.00° TCH 55

4500 4300 2680 2698

2.7 NM 2.7 NM 5 NM 3.5 1.2

CATEGORY	A	B	C	D
S-LDA/GS 6	1857-2		682 (700-2)	
S-LDA 6	1880-1 705 (800-1)		1880-2 705 (800-2)	
CIRCLING	1880-1½ 705 (800-1½)		2460-3 2800-3 1285 (1300-3) 1625 (1700-3)	

ELEV 1175 TDZE 1175

REIL Rwy 6 and 24

HIRL Rwy 6-24 and 16-34

FAF to MAP 8.5 NM

Knots	60	90	120	150	180
Min:Sec	8:30	5:40	4:15	3:24	2:50

ROANOKE, VIRGINIA

Amtd 13 05SEP24

ROANOKE/BLACKSBURG RGNL (WOODRUM FLD) (R.O.A.)

37°20'N-79°59'W

LDA Y RWY 6