

APP CRS
058°

Rwy Ldg
TDZE
1175

Apt Elev
1175

RNAV (RNP) Z RWY 6

ROANOKE/BLACKSBURG RGNL (WOODRUM FLD) (R.O.A)

RNP AR APCH - GPS.

▼


✳️ -12°C

For uncompensated Baro-VNAV systems, procedure NA below -14°C or above 54°C. For inop ALS, increase RNP 0.20 all Cats visibility to ¾ SM.

MALSR

MISSED APPROACH: (Do not exceed 240K until DEWET) Climb to 1600 then climbing right turn to 5000 direct DEWET and hold, continue climb-in-hold to 5000. *Missed approach requires minimum climb of 370 feet per NM to 2900.

ATIS 132.375	ROANOKE APP CON 133.225 339.8	ROANOKE TOWER 118.3 257.8	GND CON 121.9 257.8
------------------------	---	-------------------------------------	-------------------------------



ELEV 1175		D		TDZE 1175	
GP 3.00° TCH 58 DIXXY YONTE PKMAN MJAYY BRADB GARCA RW06 1600 5000 DEWET 112° 058° 068° 3600 3007 2587 2396 1879 91 5810 X 120 0.4% UP 9L 6800 X 150 TWR 34					
CATEGORY	A	B	C	D	
RNP 0.20 DA*		1444-½	269 (300-½)		
RNP 0.30 DA		1605-¾	430 (500-¾)		
AUTHORIZATION REQUIRED					