

WAAS
CH **86411**
W28A

APP CRS
280°

Rwy Ldg
TDZE
Apt Elev
5802
550
559

RNAV (GPS) RWY 28

FREDERICK DOUGLASS/GREATER ROCHESTER INTL (ROC)

▼

▲

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below-18°C (0°F) or above 54°C (130°F).
DME/DME RNP -0.3 NA.
Multiple unshielded lights in final approach area.
For inop MALSR, increase LPV Cats A/B visibility to RVR 5500 and Cats C/D visibility to 2.
Helicopter visibility reduction below RVR 4000 NA.

MALSR

MISSED APPROACH:
Climb to 3000 direct CEMIG and on track 262° to MONCK and hold.

ATIS 124.825	ROCHESTER APP CON 119.55 269.6	ROCHESTER TOWER 118.3 254.3	GND CON 121.7
------------------------	--	---------------------------------------	-------------------------

Procedure NA for arrivals at MAGEN on V2 eastbound.

Procedure NA for arrivals at FAULT on V31-34 southeast bound.

MSA RW 28 25 NM

MISSED APCH FIX MONCK

4 NM

ELEV 559 D TDZE 550

3000

CEMIG

tr 262°

MONCK

RW28

2100

2100

2400

BILAW

GP 3.00°

TCH 57

4.7 NM

7 NM

CATEGORY	A	B	C	D
LPV DA		820/40	270 (300-¾)	
LNAV/VNAV DA		1067-1¼	517 (500-1¼)	
LNAV MDA	1280/40	730 (800-¾)	1280-1½	730 (800-1½)
CIRCLING	1280-1	721 (800-1)	1500-2¾ 941 (1000-2¾)	1500-3 941 (1000-3)

TDZ/CL Rwy 4

REIL Rwys 7, 10 and 25

MIRL Rwy 7-25

HIRL Rwys 10-28 and 4-22

ROCHESTER, NEW YORK

Amdt 2A 05MAR15

FREDERICK DOUGLASS/GREATER ROCHESTER INTL (ROC)

43°07'N-77°40'W

RNAV (GPS) RWY 28