

WAAS
CH **45611**
W04A

APP CRS
044°

Rwy Ldg
TDZE
Apt Elev

8001
535
559

RNAV (GPS) RWY 4

FREDERICK DOUGLASS/GREATER ROCHESTER INTL (ROC)

RNP APCH - GPS.

ALSF-2

MISSED APPROACH: Climb to 1500 then climbing right turn to 3000 direct BILAW and hold.


For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -18°C or above 54°C. For inop ALS, increase LNAV Cats C/D visibility to 1 7/8 SM.

ATIS
124.825

ROCHESTER APP CON
119.55 269.6

ROCHESTER TOWER
118.3 254.3

GND CON
121.7



VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 72).

1500 3000 BILAW

FEPUG 2600

GP 3.00° TCH 56

WORIS 2000

1.9 NM to RWY 4

RWY 4

7.9 NM 2.6 NM 1.9

CATEGORY	A	B	C	D
LPV DA	735/18		200 (200-1/2)	
LNAV/VNAV DA	1290-2 1/4		755 (800-2 1/4)	
LNAV MDA	1200/24	665 (700-1/2)	1200-1 1/2	665 (700-1 1/2)
CIRCLING	1200-1	641 (700-1)	1500-2 3/4 941 (1000-2 3/4)	1500-3 941 (1000-3)

TDZ/CL Rwy 4
REIL Rws 7, 10 and 25
MIRL Rwy 7-25
HIRL Rws 10-28 and 4-22