

RNAV (GPS) RWY 10
SAVANNAH/HILTON HEAD INTL (SAV)

T For inrop ALS increase LNAV/VNAV all Cats visibility to 1½ SM, increase LNAV Cat C/D to RVR 6000. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C or above 54°C. When local altimeter setting not received, use Hilton Head Island altimeter setting and increase LPV DA to 296 feet and all visibilities to RVR 2000, increase LNAV/VNAV DA to 596 feet and all visibilities to 1¼ SM, increase all MDAs 80 feet and LNAV Cat C/D visibility to RVR 5000. For inrop ALS when using Hilton Head Island altimeter setting, LNAV/VNAV all Cats visibility to 1½ SM, increase LNAV Cat C/D visibility to 1½ SM. VDP and Baro-VNAV NA when using Hilton Head Island altimeter setting.



MISSED APPROACH:
Climb to 2500 direct
TELOE and hold.

Diagram illustrating a flight profile with various waypoints, altitudes, and distances. The profile is divided into two main sections by a vertical line, labeled R-3005C and R-3005D.

Key Waypoints and Distances:

- Top Left:** 30 NM to TILEE (NoPT), 186°, 006°, 2600, TILEE, (IAF) WOXXIT, 2600 NoPT, 186°, (5).
- Bottom Left:** 4 NM, 276°, 096°, 2600 NoPT, 006° (5), (IAF) ZUTOX, (IF/IAF) TILEE, 2000, 096° (6), 351, (FAF) SOVIE.
- Center:** 160, 180, RW10, 097°.
- Top Right:** 30 NM to WOXXIT, 186°, 276°, 2600, WOXXIT.
- Bottom Right:** 276°, ZUTOX, 2600, 006°, 30 NM to ZUTOX, 097°, 277°, 4 NM, TELOE.

Altitude and Distance Markers:

- Altitudes: 2600, 2000, 351, 160.
- Distances: 4 NM, 30 NM, 2000, 160, 180, 4 NM.

Table:

ELEV	50	D	TDZE	30
------	----	----------	------	----

[illegible]