



LOC/DME I-SYR 109.9 Chan 36	APP CRS 280°	Rwy Ldg TDZE Apt Elev	9013 413 421
---	------------------------	-----------------------------	---

ILS or LOC RWY 28
SYRACUSE HANCOCK INTL (SYR)

DME or RADAR required.		ALSF-2	MISSED APPROACH: Climb to 1100 then climbing right turn to 3000 direct SYR VORTAC and hold, continue climb-in-hold to 3000.
ATIS 124.225	SYRACUSE APP CON 126.125 269.125	SYRACUSE TOWER 120.3 239.0	GND CON 121.7 348.6



1100		3000	SYR	*LOC only	STODA I-SYR [10.3] RADAR	One Minute Holding Pattern
IM		ZIMBI I-SYR [3.4] RADAR	TILLE I-SYR [6.1] RADAR			
I-SYR [0.2] DME ANTENNA		*I-SYR [0.9]	1600	2100	2700	6000
0.2		0.9	2.5 NM	2.7 NM	4.2 NM	
CATEGORY	A	B	C	D		
S-ILS 28	613/18		200 (200-½)			
S-LOC 28	800/24		387 (400-½)		800/35 387 (400-¾)	
CIRCLING	900-1 479 (500-1)		920-1 499 (500-1)		1020-1½ 599 (600-1½)	
				1180-2½ 759 (800-2½)		