

WAAS Ch 87099 W13A	APP CRS 130°	Rwy Ldg 4559 TDZE 388 Apt Elev 390
--	------------------------	---

RNAV (GPS) RWY 13

TEXARKANA RGNL-WEBB FLD (TXK)

RNP APCH - GPS.



▼

Baro-VNAV and VDP NA when using De Queen altimeter setting. Rwy 13 helicopter visibility reduction below ¾ SM NA. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C or above 54°C. When local altimeter setting not received, use De Queen altimeter setting and increase LPV DA to 748 feet and all Cats visibility ¼ SM, LNAV/VNAV DA to 868 feet all Cats visibility ¾ SM, and all MDAs 100 feet and LNAV and Circling Cats C/D visibility ¼ SM.

⚠

MISSED APPROACH:
Climb to 2000 direct WATLE and hold.

ATIS 120.2	FORT WORTH CENTER 123.925 269.475	TEXARKANA TOWER★ 123.875 (CTAF) 0 235.625	GND CON 119.225
----------------------	---	--	---------------------------



4 NM Holding Pattern				VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 48).	2000	WATLE
6000 2000				310° 130°	2000	1.2 NM to RW13
GP 3.00° TCH 54				6.3 NM	3.8 NM	1.2 NM
CATEGORY	A	B	C	D		
LPV DA	648-¾		260 (300-¾)			
LNAV/VNAV DA	768-1		380 (400-1)			
LNAV MDA	780-1 392 (400-1)		780-1½ 392 (400-1½)			
CIRCLING	820-1 430 (500-1)	900-1 510 (600-1)	1000-1¾ 610 (700-1¾)	1080-2¼ 690 (700-2¼)		