

WAAS

CH **82119**

W19A

APP CRS

187°

Rwy Ldg

6605

TDZE

505

Apt Elev

516

RNAV (GPS) RWY 19

WACO RGNL (ACT)

RNP APCH - GPS.

▼

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -8°C or above 54°C. For inop ALS, increase LNAV/VNAV visibility all Cats to RVR 4000.

▲

ASR **RVR 1800 authorized with use of FD or AP or HUD to DA.

MALSR

AS

6

AS

6

MISSED APPROACH: Climb to 4000 direct YAYUC and on track 171° to BOSEL and hold, continue climb-in-hold to 4000.

ATIS 123.85	WACO APP CON ★ 127.65 227.125	WACO TOWER ★ 119.3 (CTAF) 0 257.8	GND CON 121.9	UNICOM 122.95
-----------------------	---	---	-------------------------	-------------------------

Procedure NA for arrivals at IMIPE on V15-54 northeast bound.

MSA RW19 25 NM
3600

ELEV 516

D

TDZE 505

187°

61

AS

6

7107 X 150

5103 X 150

TWR

★

4000

YAYUC

tr 171°

BOSEL

*LNAV only.

*1.1 NM to RW19

COFFI

2100

CHRUS

3000

GP 3.00°

TCH 55

REIL Rwy 14

HIRL Rwy 1-19 1

MIRL Rwy 14-32

CATEGORY	A	B	C	D
LPV DA**	705/24 200 (200-½)			
LNAV/VNAV DA	755/24 250 (300-½)			
LNAV MDA	900/24	395 (400-½)	900/35	395 (400-¾)
CIRCLING	940-1 424 (500-1)	980-1 464 (500-1)	1020-1½ 504 (600-1½)	1160-2 644 (700-2)

WACO, TEXAS

Amdt 1A 10AUG23

31°37'N-97°14'W

WACO RGNL (ACT)

RNAV (GPS) RWY 19