

WAAS CH 40206 W03A	APP CRS 031°	Rwy Ldg TDZE Apt Elev	7707 410 410
--	------------------------	-----------------------------	---

RNAV (GPS) Y RWY 3L

TRI-CITIES (PSC)

RNP APCH.


▼

⚠

Baro-VNAV NA when using Hermiston altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -14°C or above 54°C. VDP NA with Hermiston altimeter setting.
When local altimeter setting not received, use Hermiston altimeter setting: increase all DA 95 feet and all MDA 100 feet. Increase LPV all Cats visibility ¼ mile, LNAV/VNAV all Cats visibilities ⅓ mile: increase LNAV Cats C and D visibility ⅓ mile. Circling Cat C and D visibility ¼ mile.

MISSED APPROACH:
Climb to 1000 then climbing right turn to 3200 direct CITYS and hold.

ATIS 125.65	SPOKANE APP CON ★ 128.75 377.2	TRI-CITIES TOWER ★ 135.3 (CTAF) 0 285.55	GND CON 121.8	UNICOM 122.95
-----------------------	--	--	-------------------------	-------------------------



ELEV 410		D TDZE 410	
VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 49).		1000 3200 CITYS	
4 NM Holding Pattern		*RNAV only	
3500 ← 211° 031° →		*1.5 NM to RW03L	
GP 3.00° TCH 45		RW03L	
5.8 NM		2.4 NM	
A		B	
LPV DA		610-¾ 200 (200-¾)	
LNAV/VNAV DA		708-1 298 (300-1)	
LNAV MDA		920-1 510 (600-1)	
CIRCLING		920-1 510 (600-1)	
920-1 510 (600-1)		940-1 530 (600-1)	
1040-1¾ 630 (700-1¾)		1100-2¼ 690 (700-2¼)	