

WAAS CH 97624 W13A	APP CRS 132°	Rwy Ldg TDZE Apt Elev	5005 264 264
--	------------------------	-----------------------------	---

RNAV (GPS) RWY 13

MOTON FLD MUNI (Ø6A)


▼

NA

Baro-VNAV NA. DME/DME RNP-0.3 NA. Use Montgomery altimeter setting; when not received, use Troy Muni at N Kenneth Campbell Fld altimeter setting and increase all DA 18 feet and all MDA 20 feet; increase Circling Cats B and C visibility ¼ mile. Helicopter visibility reduction below ¾ SM NA.

MISSED APPROACH: Climb to 3000 direct ANGLES and hold.

ATLANTA APP CON★ 125.5 323.1	UNICOM 122.8 (CTAF) Ø
--	---------------------------------



ELEV 264

TDZE 264

4 NM Holding Pattern TSKGE

VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 30).

3000 ANGLES

GP 3.00° TCH 40

AIRMN 2100

CHPPE 3.2 NM to RWY13

RWY13

6.9 NM 2.4 NM 3.2 NM

*LNNAV only

*1300

CATEGORY	A	B	C	D
LPV DA		661-1⅜	397 (400-1⅜)	
LNNAV/VNAV DA		798-1⅞	534 (600-1⅞)	
LNNAV MDA	820-1	556 (600-1)	820-2⅝	556 (600-2⅝)
CIRCLING	960-1 696 (700-1)	1060-1 796 (800-1)	1200-2¾ 936 (1000-2¾)	1260-3 996 (1000-3)

MIRL Rwy 13-31 Ø