

WAAS CH 42512 W22A	APP CRS 221°	Rwy Ldg TDZE 422 Apt Elev 422
--	------------------------	---

RNAV (GPS) RWY 22

EVANSVILLE RGNL (EVV)

ASR


For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C (5°F) or above 54°C (130°F). DME/DME RNP-0.3 NA. Circling Rwy 9 NA at night.
** RVR 1800 authorized with the use of FD or AP or HUD to DA.

MALSR


MISSED APPROACH:

Climb to 2500 direct ICINU and hold.

ATIS 120.2	EVANSVILLE APP CON ★ 124.025 290.9	EVANSVILLE TOWER ★ 118.7(CTAF) 257.8	GND CON 121.9	UNICOM 122.95
----------------------	--	--	-------------------------	-------------------------



2500 ↑ ICINU	ZAGAK 2 NM to RW22		CUYAR 2500	JISEV	4 NM Holding Pattern
*LNAV only	*1.2 NM to RW22	*1100	221°	041° ←221°	2500
RW22	1.2 NM	0.8	4.4 NM	6.2 NM	GP 3.00° TCH 50
CATEGORY	A	B	C	D	
LPV DA	**622/24		200 (200-½)		
LNAV/ VNAV DA	840/45		418 (500-¾)		
LNAV MDA	860/24	438 (500-½)	860/40	438 (500-¾)	
CIRCLING	920-1 498 (500-1)	1040-1 618 (700-1)	1040-1¾ 618 (700-1¾)	1040-2 618 (700-2)	



EC-2, 03 SEP 2026 to 01 OCT 2026

EC-2, 03 SEP 2026 to 01 OCT 2026