

PACKK NINE DEPARTURE

TOP ALTITUDE:
6000

FLAT ROCK
113.3 FAK 
Chan 80

GREENSBORO
116.2 GSO 
Chan 109

LIBERTY
113.0 LIB
Chan 77

RALEIGH-DURHAM
117.2 RDU 
Chgn 119

SHPRD

NORTH DEPARTURE	132.35	256.9
-----------------	--------	-------

SPECIAL INSTRUCTIONS:
For appropriate departure
control frequency use
frequency depicted within
sector for route of flight
after RDU VORTAC.

NOTE: RADAR required.
NOTE: Turbojets only.

SOUTH DEPARTURE
125.3 353.675

TAKEOFF MINIMUMS

Rwy 14, 32: NA-ATC.
Rwys 5L/R: Standard.
Rwy 23L: Standard with minimum climb
of 250' per NM to 2300.
Rwy 23R: Standard with minimum climb
of 240' per NM to 2100.

NOTE: Chart not to scale.

(CONTINUED ON FOLLOWING PAGE)

RALEIGH/DURHAM, NORTH CAROLINA
RALEIGH-DURHAM INTL (RDU)

PACKK NINE DEPARTURE

(PACK9.RDU) 25FEB21



DEPARTURE ROUTE DESCRIPTION

TAKEOFF RUNWAYS 5L/R: Climb on heading 054°, or as assigned by ATC, thence. . . .

TAKEOFF RUNWAYS 23L/R: Climb on heading 234°, or as assigned by ATC, thence. . . .

. . . .for RADAR vectors to assigned/filed transition/fix/navaid/airway, maintain 6000, expect filed altitude ten minutes after departure.

FAYETTEVILLE TRANSITION (PACK9.FAY): From over RDU VORTAC on RDU R-215 to EVIGY, then on FAY R-360 to FAY VOR/DME.

ROZBO TRANSITION (PACK9.ROZBO): From over RDU VORTAC on RDU R-181 to ROZBO.

SHPRD TRANSITION (PACK9.SHPRD): From over RDU VORTAC on RDU R-274 and LIB R-088 to LIB VORTAC, then on LIB R-261 to SHPRD.

SE-2, 03 SEP 2026 to 01 OCT 2026

SE-2, 03 SEP 2026 to 01 OCT 2026