

WAAS CH 86214 W02A	APP CRS 019°	Rwy Ldg TDZE Apt Elev	7003 1265 1268
--	------------------------	-----------------------------	---

RNAV (GPS) RWY 2
SPRINGFIELD-BRANSON NTL (SGF)

RNP APCH - GPS.

V For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -17°C or above 54°C. Baro-VNAV and VDP NA when using HFJ altimeter setting. For inop MALSR, increase LNAV Cat A and B visibility to RVR 5000. When local altimeter setting not received, use HFJ altimeter setting: increase LPV DA to 1680 feet; increase LNAV/VNAV DA to 1844 feet and all visibilities ½ SM; increase all MDAs 100 feet and LNAV visibility Cts C/D to RVR 6000 and Circling visibility Cts C/D ½ SM. For inop ALS, increase LNAV/VNAV all Cts visibility to 1½ SM, LNAV Cts A/B to RVR 5500, and LNAV Cat D to 1½ SM.

MALSR



MISSED APPROACH: Climb to 3000 direct INOYU and hold.

ATIS 135.125	SPRINGFIELD APP CON 124.95 290.5	SPRINGFIELD TOWER 119.9 257.8	GND CON 121.9 251.15
------------------------	--	---	--------------------------------

