

NDB LLW

254

APP CRS

101°

Rwy Ldg

7219

TDZE

11

Apt Elev

11

ELIZABETH CITY CG AIR STATION/RGNL (E/C/G)

NDB RWY 10

Procedure not authorized when tethered balloon located approximately 2 miles southeast of airport is flying. When local altimeter setting not received, use Currituck altimeter setting and increase all MDA 40 feet.

SALS

A2

11

11

MISSED APPROACH: Climb to 1600 then left turn direct LLW NDB and hold.

ASOS 124.375	NORFOLK APP CON 119.55 269.425	ELIZABETH CITY TOWER★ 120.5(CTAF) 355.6	GND CON 121.9	UNICOM 122.95
-----------------	-----------------------------------	--	------------------	------------------

RADAR required for procedure entry at SWOPE.

Remain within 10 NM

1600

281°

101°

1600

LLW NDB

1600

1600

LLW

5.5 NM

ELEV 11

TDZE 11

101°

61

TWR

7219 X 150

28

04518 X 150

CATEGORY	A	B	C	D
S-10	640-1 629 (700-1)		640-1¾ 629 (700-1¾)	640-2 629 (700-2)
CIRCLING	640-1 629 (700-1)		640-1¾ 629 (700-1¾)	640-2 629 (700-2)

MIRL Rwy 1-19

HIRL Rwy 10-28

REIL Rwys 10 and 28

FAF to MAP 5.5 NM

Knots	60	90	120	150	180
Min:Sec	5:30	3:40	2:45	2:12	1:50

ELIZABETH CITY, NORTH CAROLINA

Orig-H 13AUG20

ELIZABETH CITY CG AIR STATION/RGNL (E/C/G)

36°16'N-76°10'W

NDB RWY 10