


WAAS CH 40014 W04A	APP CRS 042°	Rwy Ldg TDZE 542 Apt Elev 544
--	------------------------	---

RNAV (GPS) RWY 4
TYLER POUNDS RGNL (TYR)

RNP APCH - GPS. ⚠ For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -7°C or above 54°C. For inop ALS, increase LNAV/VNAV all Cats visibility to 1 ½ SM, LNAV all Cats visibility to 1 SM.	MALSRL MISSED APPROACH: Climb to 1100 then climbing right turn to 2500 direct OTTIF and hold.
--	--

ATIS 126.25	LONGVIEW APP CON ★ 128.75 379.15	POUNDS TOWER ★ 120.1 (CTAF) 0 257.8	GND CON 121.9	UNICOM 122.95
-----------------------	--	---	-------------------------	-------------------------



4 NM Holding Pattern IPEME		1100	2500	OTTIF
6000 ← 222° 3000 042° →		DAYAY 2200	*1 NM to RW04	*LNAV only.
GP 3.00° TCH 54		2200	RW04	
5.8 NM		4 NM	1 NM	
CATEGORY	A	B	C	D
LPV DA		742-½	200 (200-½)	
LNAV/VNAV DA		943-¾	401 (400-¾)	
LNAV MDA	920-½	378 (400-½)	920-⅝	378 (400-⅝)
CIRCLING	980-1 436 (500-1)	1020-1 476 (500-1)	1160-1¾ 616 (700-1¾)	1280-2¼ 736 (800-2¼)

