

APP CRS 219°	Rwy Ldg	4498
	TDZE	607
	Apt Elev	612

RNAV (GPS) RWY 22

MUSKOGEE-DAVIS RGNL (MKO)

⚠

DME/DME RNP-0.3 NA. When local altimeter setting not received, use Tahlequah altimeter setting: increase all MDA 100 feet and visibility LNAV and Circling Cat C ¼ SM and LNAV and Circling Cat D ½ SM. VDP NA when using Tahlequah Muni altimeter setting. Straight-in Rwy 22 NA at night, Circling Rwy 4, 18, 22, 36 NA at night. Rwy 4, 18, 22, 36 helicopter visibility reduction below 1 SM NA.

MISSED APPROACH:

Climb to 2400 direct MEKLE and hold.

ASOS 135.025	FORT WORTH CENTER 132.2 338.35	UNICOM 122.8 (CTAF) 0
------------------------	--	---------------------------------

The main chart displays the RNP-0.3 NA flight path for RNAV (GPS) RWY 22. Key features include:

- Waypoints:** JOKAT, CERKA, FEVUP, KURRE, MEKLE.
- Altitudes:** 2600, 3600, 2200, 2400, 3100, 3700, 612, 607.
- Distances:** 30 NM to JOKAT, 10 NM to JOKAT, 4 NM, 30 NM to CERKA, 10 NM to CERKA, 5 NM to KURRE, 30 NM to KURRE, 1.4 NM to RW22, 3.4 NM, 6.1 NM.
- Angles:** 129°, 039°, 219°, 309°, 039°, 219°.
- Obstacles:** 1904 X 60, 4498 X 75, 696.

ELEV 612

TDZE 607

REIL Rwy 13 0
MIRL Rwy 13-31 0

2400 MEKLE			
CERKA 4 NM Holding Pattern			
FEVUP 2200			
RW22 1.4 NM to RW22 3.4 NM 6.1 NM			
CATEGORY	A	B	C
LNAV MDA	1100-1	493 (500-1)	1100-1½ 493 (500-1½)
CIRCLING	1140-1 528 (600-1)	1180-1 568 (600-1)	1320-2 708 (800-2) 1400-2½ 788 (800-2½)

MUSKOGEE, OKLAHOMA

Orig-D 30DEC21

35°39'N-95°22'W

MUSKOGEE-DAVIS RGNL (MKO)

RNAV (GPS) RWY 22