

LOC I-JDP 108.7	APP CRS 276°	Rwy Ldg 12000 TDZE 875 Apt Elev 896
---------------------------	------------------------	--

ILS or LOC RWY 27

CINCINNATI/NORTHERN KENTUCKY INTL (CVG)



RNP APCH - GPS. From FIBSU, BREWZ, ZALD or YEYUP.
RADAR required for procedure entry at KAYDE.

MALSRL

MISSED APPROACH: Climb to 2000 then climbing left turn to 3000 direct FLM VOR/DME and hold.

For inop ALS, increase S-LOC 27 Cat C/D visibility to 1½ SM.
*RVR 1800 authorized with use of FD or AP or HUD to DA.

D-ATIS 134.375	CINCINNATI APP CON 119.7 363.15 (090°-269°) 123.875 363.15 (270°-089°)	CINCINNATI TOWER 118.975 360.85 (18L/36R) 118.3 (9/27, 18C/36C) 133.325 (18R/36L)	GND CON 121.7
--------------------------	--	---	-------------------------



2000	3000	FLM	VGSI and ILS glidepath not coincident (VGSI Angle 3.00/TCH 67°).	BLOCK INT RADAR
4.9 NM 3.6 NM				
CATEGORY	A	B	C	D
S-ILS 27*	1075/24 200 (200-½)			
S-LOC 27	1340/24	465 (500-½)	1340/50	465 (500-1)
CIRCLING	1460-1	564 (600-1)	1560-1¾ 664 (700-1¾)	1560-2 664 (700-2)

SE-1, 03 SEP 2026 to 01 OCT 2026

SE-1, 03 SEP 2026 to 01 OCT 2026