



WAAS CH 49099 W36A	APP CRS 006°	Rwy Ldg TDZE Apt Elev	8000 873 896
--	------------------------	-----------------------------	---

RNAV (GPS) Y RWY 36L
CINCINNATI/NORTHERN KENTUCKY INTL (CVG)

RNP APCH - GPS. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -13°C or above 54°C. Use of FD or AP required during simultaneous operations. Simultaneous approach authorized. LNAV procedure NA during simultaneous operations. For inop ALS, increase LNAV/VNAV all Cats visibility to RVR 5500 and LNAV Cats C and D visibility to 5500.	ALSF-2 	MISSED APPROACH: Climb to 3000 direct KRTHY and on 329° track to BATHY and hold.
---	------------	--

D-ATIS 134.375	CINCINNATI APP CON 119.7 363.15 (090°-269°) 123.875 363.15 (270°-089°)	CINCINNATI TOWER 118.975 360.85 (18L/36R) 118.3 (9/27, 18C/36C) 133.325 (18R/36L)	GND CON 121.7
--------------------------	--	---	-------------------------



BEPEE			
4000 006°			
GP 3.00° TCH 55			
4.9 NM 3.3 NM 0.7 NM 1 NM			
CATEGORY	A	B	C
LPV DA	1073/18	200 (200-1/2)	
LNAV/VNAV DA	1240/35	367 (400-5/8)	
LNAV MDA	1240/24	367 (400-1/2)	1240/35 367 (400-5/8)
CIRCLING	1460-1	564 (600-1)	1560-1 3/4 664 (700-1 3/4)

SE-1, 03 SEP 2026 to 01 OCT 2026

SE-1, 03 SEP 2026 to 01 OCT 2026